GEP WATER LOCKS

Automatische afsluiting van waterleiding







PRODUCT DESCRIPTION


The GEP Water Lock is a leak detection and control system for water systems. If the sensor comes into contact with water, you will hear an audible alarm. At the same time, it automatically closes the drinking water supply. The GEP Water Lock 1/2 " consists of a metal ball valve with motor drive. It is connected to the detector unit via a flexible connection cable. The whole works on one normal 9 Volt battery and is therefore independent from the mains. The GEP Water Lock can be used for rainwater systems that are installed below the sewerage level. (For example, in a basement). Of course it can also be used to protect areas and appliances other than rain water systems against water damage. The GEP Waterlocks 3/4 "and 1" are suitable for the protection of water pipes with a diameter larger than 15 mm, such as the GEP Water Managers IRM®- 5,6,7 and 8. The GEP Water Lock $3/4\ ^{\prime\prime}$ and $1\ ^{\prime\prime}$ is a complete set consisting of a control, separate water sensor with 2 meter cable, solenoid valve and gaskets. When water is detected by the sensor, an audible alarm follows from the control unit. And the water pipe is closed by the solenoid valve. In addition, there is also the possibility of supplying the voltage supply of the appliance to be protected via the water seal. In the event of an alarm, the power of the device is switched off automatically.


SCOPE

Everywhere pipes have to be closed as soon as moisture is detected.

TECHNICAL DATA

GEP Water lock type: Water lock 1/2 " Water lock 3/4 "and 1" Alarm Acoustic: Buzzer (92 dB) Buzzer (92 dB) Detection: Built-in moisture sensor Loose moisture sensor Standing or lying on the floor Plaating: Lying on the floor or in assembly piece Height x width x depth in mm: 90 x 65 x 25 110 x 65 x 45 Shut off valve: Motor-controlled Reeled Working principle: Rotatable ball valve Solenoid valve Pipe connection: 1/2" 3/4 "or 1" 230 V / 50 Hz Food: 9 volt battery (included) CE 89/336 EWG quality mark: Connection piece in mm: <50 mm N/A





SCOPE OF DELIVERY

Product consists of: water lock 1/2 "- 3/4" - 1 ", buzzer, humidity sensor (option: mounting piece), shut-offvalve, power supply and installation instructions.

ORDERING INFORMATION

Art nr NAME PG 402123 Water lock 1/2 " including detection point 1 402124 Water lock 3/4 " including detection point 1 402125 Water lock 1 " including detection point 1 402234 IRM®-1 water lock 1 402138 IRM® 3/5 water lock 1				
402124 Water lock 3/4" including detection point 1 402125 Water lock 1" including detection point 1 402234 IRM®-1 water lock 1	Art nr	NAME	PG	
402125 Water lock 1" including detection point 1 402234 IRM®-1 water lock 1 1	402123	Water lock 1/2 " including detection point	1	
402234 IRM®-1 water lock 1	402124	Water lock 3/4" including detection point	1	
	402125	Water lock 1 " including detection point	1	
402138 IRM® 3/5 water lock 1	402234	IRM®-1 water lock	1	
	402138	IRM® 3/5 water lock	1	